

OPERATING CHARACTERIST	ICS AT 25°C	AMBIEN	Г			
LED CHARACTERISTICS	COLOR	MIN,	TYP.	MAX.	UNITS	TEST CONDITIONS
	GREEN	6.5	14.0			l 20 mA
LUMINOUS INTENSITY	BLUE	3.8	8.5		mc d	lf = 20 mA
	GREEN		565			
PEAK WAVELENGTH	BLUE		428		nm	
DOMINANT WAVELENGTH	GREEN		569			
DOMINANI WAVELENGIH	BLUE		465		nm	
	GREEN		2.1	2.5	v	lr = 20 mA
FORWARD VOLTAGE	BLUE		4.0	4.8	v	17 - 20 MA
VIEWING ANGLE	ALL		60		DEGREE	

ABSOLUTE MAXIMUM RATINGS AT 25°C AMBIENT	CO	UNITS	
ADSOLUTE MAXIMUM RATINGS AT 25 C AMDTENT	GREEN	BLUE	
POWER DISSIPATION	75	100	mW
PEAK FORWARD CURRENT (1/10 DUTY CYCLE, 0.1ms PULSE WIDTH)	90	50	mA
CONTINUOUS FORWARD CURRENT	30	20	mA
LINEAR DERATING FROM 50°C FOR GREEN / 30°C FOR BLUE	0.4	0.3	mA/°C
LEAD SOLDERING TEMPERATURE (.063" [1.6mm] FROM BODY) FOR 5 SEC.	260		°C
OPERATING TEMPERATURE	-20 TO +80		°C
STORAGE TEMPERATURE	-30 TO +100		°C


NOTES:

- I. EPOXY COLOR: WHITE DIFFUSED.
- 2. LED DIE: InGaN GREEN AND BLUE.
- 3. LEAD SPACING MEASURED NEAR EPOXY PACKAGE.
- 5. DIALIGHT PART NUMBER: 521-8012F.
- STORAGE IN ACCORDANCE WITH IPC-A-610.

PIN 2 BLUE CATHODE CATHODE
LED SCHEMATIC



ECN NO	REVISIONS	DRN	CKD	APP	DATE
	NEW RELEASE	AJF	KLJ	NO	6-25-10



4. PIN NUMBERS ARE FOR REFERENCE ONLY, DESIGNATION NON-EXISTENT ON PART.

6. THIS ASSEMBLY CONTAINS ELECTROSTATIC DISCHARGE SENSITIVE DEVICES (ESDS). MAINTAIN ALL PRECAUTIONARY MEASURES DURING ASSEMBLY, HANDLING AND

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT, REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT,				
SCALE: 8.000	DRAWING NUMBER	REV		
ALL DIM'S IN; INCHES (MM)	C-17852			
TOLERANCES: UNLESS OTHERWISE SPECIFIED	C-17052	A		
FRACTIONS: ±1/64 DECIMALS (,XX); ±.02 DECIMALS (,XXX); ±.010	TITLE Ø 3mm GREEN/BLUE BI-COLOR LED			
ANGLES: ±1°	MATERIAL -			
FINISH: -	Dialight 1501 ROUTE			
fscm 83330	SHEET I OF I FAMILY TABLE:			