



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
6832	5.0	.060	.050	0.63	100,000	C-2R
6152	5.0	.060	.150	1.89	5,000	C-2R
7132	5.0	.075	.090	1.13	25,000	C-2R
7152	5.0	.115	.150	1.89	40,000	C-2R

NOTES:

- GLASS ENVELOPE TO BE OF TIPLESS AND SEAMLESS CONSTRUCTION TO PROVIDE UNDISTORTED END VIEWING.
- WIRE TERMINALS TO BE TINNED DUMENT TYPE WIRE. OPTIONAL PLATING MATERIALS ARE AVAILABLE.
- ALL LAMPS TO BE 100% AGED FOR AN EQUIVALENT OF TEN HOURS OF THE RATED VOLTAGES.
- FINAL INSPECTION ON ALL LAMPS TO BE MIL. STD. 105-E. ELECTRICAL CHARACTERISTICS TO AN AQL OF 2.5 OR BETTER, LEVEL II. MECHANICAL TO AN AQL OF 4.0, LEVEL S-1. (NOTE: AS15 TYPE LAMPS WILL BE 100% INSPECTED FOR AMPERAGE AND MSCP RATINGS.)
- ALL DIMENSIONS PROVIDED HEREIN, NOT LISTING TOLERANCES, ARE CONSIDERED REFERENCE DIMENSIONS ONLY.

				<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
						TITLE <b>T-1 SHORTY WIRE TERMINAL LAMP</b>					
C	DIM. CHNG. 0.8±0.13 TO 0.8 REF.	5/21/01				SIZE	FSCM NO.	DRAWING NO.	<b>WIRE TERMINAL SHORTY T-1</b>		
B	LEAD DIA. 0.25 TO 0.25 REF.	02/08/00	DRAWN BY	APP'VD BY	DATE	<b>A</b>	<b>55335</b>				
A	DRAWING TO CAD - LAMPS 2022, 6802 DELETED	01/14/00	L. WENGSTROM	QC	5/21/01						
	RELEASED	07/07/97	- CAD DRAWING -			SCALE		RELEASED DATE	REVISION DATE	REV. NO.	SHEET
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	MANUAL REVISIONS NOT PERMITTED			NONE		07/07/97	5/21/01	<b>C</b>	1 OF 1